

(19) World Intellectual Property Organization
International Bureau



INTERNATIONAL PATENT COOPERATION TREATY (PCT)



(43) International Publication Date
8 February 2001 (08.02.2001)

PCT

(10) International Publication Number
WO 01/08525 A1

- (51) International Patent Classification⁷: A43C 7/04
- (21) International Application Number: PCT/CA99/00903
- (22) International Filing Date:
30 September 1999 (30.09.1999)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2,279,111 29 July 1999 (29.07.1999) CA
- (71) Applicant: LACE TECHNOLOGIES INC. [CA/CA];
2189 King Road, P.O. Box #520, King City, Ontario L7B
1G3 (CA).
- (72) Inventors: DICKIE, Robert, G.; 15 Valley Trail, New-
market, Ontario L3Y 4V8 (CA). KARABIN, Walter; 12
Cousins Drive, Aurora, Ontario L4G 1B3 (CA).
- (74) Agent: HEWSON, Donald, E.; Marks & Clerk, Suite #13,
2145 Dunwin Drive, Mississauga, Ontario L5L 4L9 (CA).
- (81) Designated States (*national*): AE, AL, AM, AT, AU, AZ,
BA, BB, BG, BR, BY, CH, CN, CR, CU, CZ, DE, DK, DM,
EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN,
IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV,
MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU,
SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ,
VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent
(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent
(AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU,
MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:
— With international search report.
— With amended claims and statement.
- For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: POSITIVE LACE ZONE ISOLATION LOCK SYSTEM AND METHOD



(57) Abstract: A positive lace zone tension isolation device and method for use with laced footwear including a base (12), an opposed, pivotable cam (14) for clamping interposed laces against the underlying base (12) and isolating the selected lace tension against migration at that point.

WO 01/08525 A1




FIG. 1




FIG. 4




FIG. 2




FIG. 3




FIG. 5

2/2




FIG. 6




FIG. 7




FIG. 8